


Termostati

Kapilarni termostat

10.10.015

KT-165 AOJ



Tmax = 65 °C
Dužina osovine: 23 mm
Dužina kapilare: 650 mm
16 (4) A, 250 V ~
Metalflex, Slovenija

Kapilarni termostat

10.10.016

KT-165 AOA



Tmax = 75 °C
Dužina osovine: 23 mm
Dužina kapilare: 650 mm
16 (4) A, 250 V ~
Metalflex, Slovenija

Kapilarni termostat

10.10.023

KT-165 77/15



Tmax = 77 °C
Dužina osovine: 15 mm
Dužina kapilare: 650 mm
16 (4) A, 250 V ~
Metalflex, Slovenija

Kapilarni termostat

10.10.024

KT-165 85/23



Tmax = 85 °C
Dužina osovine: 23 mm
Dužina kapilare: 650 mm
16 (4) A, 250 V ~
Metalflex, Slovenija

Kapilarni termostat

10.10.027

KT-165 90/15



Tmax = 90 °C
Dužina osovine: 15 mm
Dužina kapilare: 650 mm
16 (4) A, 250 V ~
Metalflex, Slovenija

Kapilarni termostat

10.10.028

NT-112 EM / 2



Tmax = 77 °C
Dužina osovine: 15 mm
Dužina kapilare: 650 mm
16 A, 400 V ~
Tecasa, Španija

AKCIJA

Kapilarni termostat

10.10.029

NT-112 EM / 1



Tmax = 85 °C
Dužina osovine: 23 mm
Dužina kapilare: 650 mm
16 A, 400 V ~
Tecasa, Španija

AKCIJA

Kapilarni termostat

10.10.251

KT-165 BTA



3 kontakta
Tmax = 85 °C
Dužina osovine: 23 mm
Dužina kapilare: 1350 mm
16 A, 250 V ~
Metalflex, Slovenija

Kapilarni termostat, sigurnosni

10.10.032

KV-441 D



Tiz = 115 - 10 °C
Sa pločicom za montažu
Dužina kapilare: 600 mm
16 A, 250 V ~
Metalflex, Slovenija

Kapilarni termostat, sigurnosni

10.10.033

KV-441 01



Tiz = 99 - 10 °C
Sa provodnicima
Dužina kapilare: 600 mm
16 A, 250 V ~
Metalflex, Slovenija

T e r m o s t a t i

Štapni termostat sa polugom

10.10.043

TRS 77 - ubodni



Tmax = 65°C
Tiz = 75°C
Dužina sonde: 275 mm
20 A, 250 V ~
V.E.B.E. Italija

Štapni termostat

10.10.045

TRS 77 - ubodni



Tmax = 65°C
Tiz = 75°C
Dužina sonde: 275 mm
20 A, 250 V ~
V.E.B.E. Italija



Štapni termostat

10.10.046

Thermowatt R-T-S 3



Tmax = 65°C
Tiz = 75°C
Dužina sonde: 280 mm
16 A, 250 V ~
Thermowatt, Italija

Štapni termostat

10.10.047

Thermowatt T-E-S



Tmax = 75°C
Tiz = 84°C
Dužina sonde: 280 mm
20 A, 220 V ~
Thermowatt, Italija

Štapni termostat

10.10.048

Thermowatt R-T-M



Tmax = 73°C

Dužina sonde: 275 mm
15A, 250 V ~
Thermowatt, Italija



Štapni termostat

10.10.049

DT 127



Tmax = 75°C
Tiz = 85°C
Dužina sonde: 280 mm
16A, 220 V ~
Metalflex, Slovenija

Kapilarni termostat

10.10.060

711.11338.00A



3 kontakta
Tmax = 90°C
Dužina osovine: 14 mm
Dužina kapilare: 1500mm
16 A, 250 V ~
T&G, Italija

Kapilarni termostat

10.10.061

711.71338.00A



3 kontakta
Tmax = 120°C
Dužina osovine: 14 mm
Dužina kapilare: 1500mm
16A, 250 V ~
T&G, Italija

Kapilarni termostat

10.10.200

711.G1339.00A



3 kontakta
Tmax = 210°C
Dužina osovine: 14 mm
Dužina kapilare: 1500mm
16 A, 250 V ~
T&G, Italija

Kapilarni termostat

10.10.440

712.10228.00A



Tmax = 90°C
Regulacija na šraf
Dužina kapilare: 1000mm
16 A, 250 V ~
T&G, Italija

T e r m o s t a t i

Kapilarni termostat

10.10.442



712.10328.00A
3 kontakta
Tmax = 90°C
Regulacija na šraf
Dužina kapilare: 1000mm
16 A, 250 V ~
T&G, Italija

Kapilarni termostat, sigurnosni

10.10.444



961.90328.00A
Opseg = 70 + 90°C
Manualno podešavanje
Dužina kapilare: 1000mm
16 A, 250 V ~
T&G, Italija

Nalegajući termostat

10.10.400



7C1.1R306.50A
Tmax = 90°C
Diferenca: 6 ± 2°C
16 A, 250 V ~
T&G, Italija

Nalegajući termostat

10.10.410



7A1.1R306.00A
bimetalni
Tmax = 90°C
Diferenca: 8 ± 2°C
16 A, 250 V ~
T&G, Italija

Kapilarni termostat

10.10.122



KT 165 AMA
Termostat za veš mašinu
Gorenje
16 A, 250 V ~
Metalflex, Slovenija

Kapilarni termostat

10.10.121



KT 165 BCA
Termostat za veš mašinu
Obod Novi Tip
16 A, 250 V ~
Metalflex, Slovenija

Kapilarni termostat

10.10.125



KT 165 BUB
3 kontakta
Termostat za veš mašinu
Candy, Whirlpool,
Ariston, Beko, ...
16 A, 250 V ~
Metalflex, Slovenija

Kapilarni termostat

10.10.211



KT-165 CBA
Termostat za štednjak
Opseg: 50 + 320°C
Dužina osovine: 18 mm
Dužina kapilare: 1050 mm
15A, 250 V ~
Metalflex, Slovenija

Kapilarni termostat

10.10.215



KT-165 400°C
Termostat za pizza peč
Opseg: 80 + 400°C
Dužina osovine: 18 mm
Dužina kapilare: 1050 mm
15 A, 250 V ~
Metalflex, Slovenija

Kapilarni termostat

10.10.220



KT-165 CLB
Termostat štednjaka
Opseg: 50 + 285°C
Dužina osovine: 23 mm
Dužina kapilare: 1000 mm
15 A, 250 V ~
Metalflex, Slovenija

Termostati

Kapilarni termostat

10.10.222

KT-165 CLA

Termostat štednjaka

Opseg: 50 + 300°C

Dužina osovine: 23 mm

Dužina kapilare: 1000 mm

15 A, 250 V ~

Metalflex, Slovenija



Kapilarni termostat

10.10.223

KT-165 CL2A

Termostat štednjaka

Opseg: 50 + 250°C

Dužina osovine: 45 mm

Dužina kapilare: 1000 mm

15 A, 250 V ~

Metalflex, Slovenija



Termostat kvarcne grejalice

10.10.700

Kapilarni



MMG, Mađarska

Bimetalni termostat

10.10.124

AV4817

NO 65, NZ 85

Termostat za mašinu

za pranje posuđa

Merloni Smeg



Termostat za automatsku grejnu ploču

10.10.600



ETA, Slovenija

Bimetalni termostat

10.10.123

CY4802

NO 30, NZ 84

Termostat za veš mašinu

Candy



Termostat kvarcne grejalice

10.10.005

Bimetalni



T e r m o s t a t i

Kapilarni termostat

10.10.601

55.13012.106




T = 30 ± 85°C
Dužina sonde = 92 mm
Debljina sonde: ø6
Dužina kapilare: 830 mm
ETA, Slovenija

Trofazni termostat

10.10.602

55.34042.020




T = 60 ± 230°C
Dužina sonde = 226 mm
Debljina sonde: ø3,1
Dužina kapilare: 880 mm
ETA, Slovenija

Trofazni termostat

10.10.603

55.34032.103




Sa navojnim priključkom
T = 89 ± 223°C
Dužina sonde = 231 mm
Debljina sonde: ø4
Dužina kapilare: 880 mm
ETA, Slovenija

Trofazni termostat sa predprekidačem

10.10.604

55.34642.101




Sa navojnim priključkom
T = 89 ± 223°C
Dužina sonde = 231 mm
Debljina sonde: ø4
Dužina kapilare: 880 mm
ETA, Slovenija

Trofazni termostat

10.10.605

55.34062.102




Sa navojnim priključkom
T = 56 ± 326°C
Dužina sonde = 226 mm
Debljina sonde: ø3,1
Dužina kapilare: 880 mm
ETA, Slovenija

Trofazni termostat

10.10.606

55.34062.101




T = 100 ± 350°C
Dužina sonde = 77 mm
Debljina sonde: ø6
Dužina kapilare: 880 mm
ETA, Slovenija

Trofazni termostat sa predprekidačem

10.10.607

55.34662.103




T = 56 ± 326°C
Dužina sonde = 226 mm
Debljina sonde: ø3,1
Dužina kapilare: 880 mm
ETA, Slovenija

Trofazni termostat za TA peć CER

10.10.610

55.34052.102




T = 64 ± 281°C
Dužina sonde = 226 mm
Debljina sonde: ø3,1
Dužina kapilare: 880 mm
ETA, Slovenija

Kapilarni termostat

10.10.620

55.13072.130



Opseg: 100 ± 400°C
Dužina sonde = 163 mm
Debljina sonde: ø5
Dužina kapilare: 830 mm
ETA, Slovenija

Kapilarni termostat

10.10.618

55.13062.104



Opseg: 50 ± 320°C
Dužina sonde = 59 mm
Debljina sonde: ø6
Dužina kapilare: 850 mm
ETA, Slovenija

NOVO !!!

NOVO !!!

Termostati

Monofazni termostat

10.10.720 20 ÷ 110°C



20 A, 250 V ~
MMG, Mađarska

Monofazni termostat

10.10.721 50 ÷ 210°C



20 A, 250 V ~
MMG, Mađarska

Trofazni termostat


10.10.710 20 ÷ 110°C



16 A, 400 V ~
MMG, Mađarska

Trofazni termostat

10.10.705 50 ÷ 230°C



16 A, 400 V ~
MMG, Mađarska

Trofazni termostat

10.10.704 50 ÷ 280°C



16 A, 400 V ~
MMG, Mađarska

Trofazni termostat

10.10.703 50 ÷ 320°C



16 A, 400 V ~
MMG, Mađarska

Trofazni termostat, sigurnosni

10.10.724 Tiz = 250°C



16 A, 400 V ~
MMG, Mađarska

Trofazni termostat, sigurnosni

10.10.725 Tiz = 315°C



16 A, 400 V ~
MMG, Mađarska

Trofazni trostepeni termostat

10.10.701 80 / 85 / 90°C
P1: 20 ÷ 80°C
P2: 25 ÷ 85°C
P3: 30 ÷ 90°C



16 A, 400 V ~
MMG, Mađarska

Termostati

Termički osigurač

10.10.976

TV 433 L1



Tiz = 117°C
Dužina provodnika:
355 mm
16 A, 220 V ~
Metalflex, Slovenija

Termički osigurač

10.10.975

TV 433 L7



Tiz = 117°C
Dužina provodnika:
L1=355 mm, L2=910mm
16 A, 220 V ~
Metalflex, Slovenija

Termički osigurač

10.10.971



Tiz = 98°C
Dužina provodnika:
355 mm
16 A, 220 V ~
ATTOS

T e r m o s t a t i

Termostat za rashladne uređaje

10.10.300



GE 205A45
Termostat za frižider
H (On/Off) -17°C / -28°C
T (On/Off) -1°C / -7,5°C

Dužina kapilare: 1200mm
General Electric, Italija

Termostat za rashladne uređaje

10.10.301



077B0973
Termostat za frižider
H (On/Off) -15°C / -24,7°C
T (On/Off) -6°C / -14°C

Dužina kapilare: 850 mm
Biterm, Slovenija

Termostat za rashladne uređaje

10.10.302



GE 205A113
Termostat za frižider
H (On/Off) -17°C / -28°C *
T (On/Off) -1°C / -7,5°C *

Dužina kapilare: 1000mm
General Electric, Italija

Termostat za rashladne uređaje

10.10.303



077B4047
Za frižider sa iglicom
H (On/Off) -11°C / -22°C
T (On/Off) -4°C / -13°C
O 6°C / 6°C

Dužina kapilare: 1000mm
Biterm, Slovenija

Termostat za rashladne uređaje

10.10.305



GE 205A46
Za rashladnu vitrinu
H (On/Off) 2°C / -3,4°C *
T (On/Off) 10,5°C / 2,7°C

Dužina kapilare: 1500mm
General Electric, Italija

Termostat za rashladne uređaje

10.10.306



077B2293
Za vertikalni zamrzivač
H (On/Off) -21°C / -28°C
T (On/Off) -15° / -21°C
S (On/Off) -12°C / -18°C
Dužina kapilare: 1900mm
Biterm, Slovenija

Termostat za rashladne uređaje

10.10.307



GE 205A115
Termostat za frižider
H (On/Off) 2°C / -3,4°C *
T (On/Off) -1°C / -7,5°C *

Dužina kapilare: 1000mm
General Electric, Italija

Termostat za rashladne uređaje

10.10.312



077B2219
Za horizontalni zamrzivač
H (On/Off) -15°C / -28°C
T (On/Off) -15°C / -21°C
S (On/Off) -12°C / -18°C
Dužina kapilare: 900mm
Biterm, Slovenija

Termostat za rashladne uređaje

10.10.310



GE 207A47
Termostat za zamrzivač
H (On/Off) -17°C / -27°C *
T (On/Off) -10°C / -20°C *
S (On/Off) -8°C / -15°C *
Dužina kapilare: 1000mm
General Electric, Italija

Termostat za rashladne uređaje

10.10.322



077B6120
Termostat kombinacije
H (On/Off) -9°C / -27°C
T 3,7°C / 3,7°C
2 kontakta
Dužina kapilare: 920mm
Biterm, Slovenija

T e r m o s t a t i

Termostat za rashladne uređaje

10.10.320



GE 229A70
Termostat kombinacije
H (On/Off) 3°C / -29°C
T (On/Off) 3°C / -11°C

Dužina kapilare: 1200mm
General Electric, Italija

Termostat za rashladne uređaje

10.10.323



077B6598
Termostat kombinacije
H (On/Off) -9°C / -27°C
T 3,7°C / 3,7°C

3 kontakta
Dužina kapilare: 920mm
Biterm, Slovenija

Termostat za rashladne uređaje

10.10.325



GE 229A149
Termostat kombinacije
H (On/Off) 3°C / -29°C *
T (On/Off) 3°C / -29°C *

3 kontakta
Dužina kapilare: 800 mm
General Electric, Italija

Termostat za rashladne uređaje

10.10.324



481927128788
Kombinacija ATEA
H (On/Off) -13°C / -26°C
T 3,7°C / 3,7°C

3 kontakta
Dužina kapilare: 1000mm
ATEA, Italija

Termostat za rashladne uređaje

10.10.308



RANCO K-50
Termostat frižidera
H (On/Off) -14,5°C / -23°C
T (On/Off) 2°C / -8°C

2 kontakta
Dužina kapilare: 1200mm
RANCO, Italija

Termostat za rashladne uređaje

10.10.313



RANCO K-54
Uspravni zamrzivač
H (On/Off) -29°C / -34°C
T (On/Off) -12°C / -16,5°C

3 kontakta
Dužina kapilare: 2000mm
RANCO, Italija

Termostat za rashladne uređaje

10.10.314



RANCO K-54
Horizontalni zamrzivač
H (On/Off) -25°C / -30°C
T (On/Off) -12°C / -16,5°C

3 kontakta
Dužina kapilare: 1000mm
RANCO, Italija

Termostat za rashladne uređaje

10.10.326



RANCO K-59
Termostat kombinacije
H (On/Off) 3,5°C / -26°C
T (On/Off) 3,5°C / -11°C

3 kontakta
Dužina kapilare: 1200mm

Termostat za rashladne uređaje

10.10.315



RANCO K-60
Za frižider sa iglicom
H (On/Off) -20°C / -25°C *

T (On/Off) -4°C / -10,4°C
Otapanje: 5,5°C
Dužina kapilare: 1200mm
RANCO, Italija