

# I/O Extender™

Input/Output Extender for  
WEB•HOME™



## Features:

- 3 relay outputs, 230V, 2A
- 3 inputs
- LED indicator for status/fault

## WEB•HOME™ – now with I/O Extender™

WEB•HOME™ is expanding the possibilities which gives internet operated heating control users more options for control and monitoring. By adding one I/O Extender™ to a WEB•HOME™ system you expand the number of inputs by 3 and relay outputs by 3, giving you a total of 4 inputs and 4 outputs.

You can add up to 5 I/O Extender™ to one WEB•HOME™ system.

This means that the user can sit faraway from his WEB•HOME™ system and control, monitor, and operate his electrical heating system, water heater, alarm system, outdoor lights, swimming pool temperature, swimming pool dehumidifier, etc.

DEVI A/S  
Ulvehavevej 61  
7100 Vejle  
Telf.: 76 42 47 00  
Fax: 76 42 47 01  
www.devi.com

**DEVI** ™

Member of the Danfoss Group

Technical data	
Operation voltage	24 VDC $\pm$ 10%
Power consumption	< 1W
Relays: • Resistive load • Inductive load	230V <sub>AC</sub> 2A cos $\varphi$ = 0.3 Max. 1A
IP Class	20
Ambient temperature	-10 – 55°C
Size D/H/W	53/86/70
Inputs: • 1 Input • 2 Inputs, configurable	230V - Temperature -25°C – 75°C (DEVI NTC floor sensor) - Digital (0-5VDC)

### Connection diagram

