



**checkweigher**

**EC-M**

## Equipment

- Digital electronic system
- touch screen control panel (LCD) da 5,7"
- Electronic self-calibration device
- Production data management in conformity with the standards in force
- Speed adjustable from keypad
- Commands protected by password
- 50 storable product programs
- Conveyors easily and quickly removable
- Electrodynamic compensation Load Cell

## Accessories

- Ejection systems
- Reject management systems
- speed accelerating conveyors
- Wind-prevention tunnel
- Air pressure control
- APS Statistic kit whit printer
- Open flap control device
- Data collection via network
- Conformity with standards ISO-FDA-HACCP
- Validation documents (IQ, OQ)

## Technical specifications

Capacity	750 g
Linear speed	up to 100 m/1'
Output	up to 230 ppm
Display division	0,1 g
Accuracy from	± 0,5 g
Pneumatic supply	0,6 Mpa
Air consumption (for ejection)	0,5 NI
Power supply	L1/N/PE 230/115V - 50/60Hz
Power absorption	0,8 kVA
Version	Stainless steel, Alluminium anodized / painted
Protection	IP65
Weight	90 kg

## EC-M

Technical drawing showing side and top views of the checkweigher. The side view indicates a height of  $H_{pl}$  and a width of 400. The top view shows a width of 150 and is divided into sections A, B, and C. A red arrow indicates the direction of flow.

Infeed	Weighing	Outfeed
A	B	C
300	200	400
400	250	500
-	300	-



© 2002 - 2005 PRISMA INDUSTRIALE - REV 09/2005



Prisma Industriale S.r.l.

• Via La Bionda, 17 - 43036 Fidenza - Parma - Italy • Tel. +39 0524 527270 - Fax +39 0524 524142  
 • www.prismaindustriale.com • info@prismaindustriale.com

Data appearing in this brochure may be modified without prior warning.  
 The machine used in this document is with all options