










 <p><small>Werkstoff NBR von -40° bis 100°C DIN 3760 ISO 6194</small></p>	<p><b>Oil seal 100x120x12 mm</b> Shaft seal with dust lip AO</p> <p>ABMS. d 100 x D 120 x W 12 mm</p> <p>NBR -40 ° to 100 ° C for sealing rotating shafts and axles sealed in a radial direction for both right and left rotation</p> <p>International German Standard DIN ISO 3 760 6 194</p>
 <p><small>Werkstoff NBR von -40° bis 100°C DIN 3760 ISO 6194</small></p>	<p><b>Oil seal 100x130x12 mm</b> Shaft seal with dust lip AO</p> <p>ABMS. d 100 x D 130 x W 12 mm</p> <p>NBR -40 ° to 100 ° C for sealing rotating shafts and axles sealed in a radial direction for both right and left rotation</p> <p>German standard DIN 3760 International Standard ISO 6194</p>
	<p><b>Oil Seal 12x19x5mm</b> Shaft seal with dust lip AO</p> <p>ABMS. d 12 x D 19 x W 5</p> <p>NBR -40 ° to 100 ° C for sealing rotating shafts and axles sealed in a radial direction for both right and left rotation</p> <p>German standard DIN 3760 International Standard ISO 6194</p>
 <p><small>Werkstoff NBR von -40° bis 100°C DIN 3760 ISO 6194</small></p>	<p><b>Oil Seal 12x24x7 mm</b> Shaft seal with dust lip AO</p> <p>ABMS. d 12 x D 24 x W 7</p> <p>NBR -40 ° to 100 ° C for sealing rotating shafts and axles sealed in a radial direction for both right and left rotation</p>

	German standard DIN 3760 International Standard ISO 6194
	<p><b>Oil Seal 12x26x7 mm</b> Shaft seal with dust lip AO</p> <p>ABMS. d 12 x D 26 x W 7</p> <p>NBR -40 ° to 100 ° C for sealing rotating shafts and axles sealed in a radial direction for both right and left rotation</p> <p>German standard DIN 3760 International Standard ISO 6194</p>
	<p><b>Oil Seal 15x35x7 mm</b> Shaft seal with dust lip AO</p> <p>ABMS. d 15 x D 35 x W 7</p> <p>NBR -40 ° to 100 ° C for sealing rotating shafts and axles sealed in a radial direction for both right and left rotation</p> <p>German standard DIN 3760 International Standard ISO 6194</p>
	<p><b>Oil Seal 25x42x7 mm</b> Shaft seal with dust lip AO</p> <p>ABMS. d 25 x D 42 x W 7</p> <p>NBR -40 ° to 100 ° C for sealing rotating shafts and axles sealed in a radial direction for both right and left rotation</p> <p>German standard DIN 3760 International Standard ISO 6194</p>
	<p><b>Oil Seal 28x47x7 mm</b> Shaft seal with dust lip AO</p> <p>ABMS. d 28 x D 47 x W 7</p> <p>NBR -40 ° to 100 ° C for sealing rotating shafts and axles sealed in a radial direction for both right and left rotation</p>

	German standard DIN 3760 International Standard ISO 6194
	<p><b>Oil Seal 30X47X7 mm</b> Shaft seal with dust lip AO</p> <p>ABMS. d 30 x D 47 x W 7</p> <p>NBR -40 ° to 100 ° C for sealing rotating shafts and axles sealed in a radial direction for both right and left rotation</p> <p>German standard DIN 3760 International Standard ISO 6194</p>
	<p><b>Oil Seal 30x55x7 mm</b> Shaft seal with dust lip AO</p> <p>ABMS. d 30 x D 55 x W 7</p> <p>NBR -40 ° to 100 ° C for sealing rotating shafts and axles sealed in a radial direction for both right and left rotation</p> <p>German standard DIN 3760 International Standard ISO 6194</p>
	<p><b>Oil Seal 32x45x7 mm</b> Shaft seal with dust lip AO</p> <p>ABMS. d 32 x D 45 x W 7</p> <p>NBR -40 ° to 100 ° C for sealing rotating shafts and axles sealed in a radial direction for both right and left rotation</p> <p>German standard DIN 3760 International Standard ISO 6194</p>
	<p><b>Oil Seal 32x52x7 mm</b> Shaft seal with dust lip AO</p> <p>ABMS. d 32 x D 52 x W 7</p> <p>NBR -40 ° to 100 ° C for sealing rotating shafts and axles</p>

	<p>sealed in a radial direction for both right and left rotation</p> <p>German standard DIN 3760 International Standard ISO 6194</p>
	<p><b>Oil Seal 32x58x8 mm</b> Shaft seal with dust lip AO</p> <p>ABMS. d 32 x D 58 x W 8</p> <p>NBR -40 ° to 100 ° C for sealing rotating shafts and axles sealed in a radial direction for both right and left rotation</p> <p>German standard DIN 3760 International Standard ISO 6194</p>
	<p><b>Oil Seal 35x47x7 mm</b> Shaft seal with dust lip AO</p> <p>ABMS. d 35 x D 47 x W 7</p> <p>NBR -40 ° to 100 ° C for sealing rotating shafts and axles sealed in a radial direction for both right and left rotation</p> <p>German standard DIN 3760 International Standard ISO 6194</p>
	<p><b>Oil seal 35x52x10 mm</b> Shaft seal with dust lip AO</p> <p>ABMS. d 35 x D 52 x W 10 mm</p> <p>NBR -40 ° to 100 ° C for sealing rotating shafts and axles sealed in a radial direction for both right and left rotation</p> <p>German standard DIN 3760 International Standard ISO 6194</p>
	<p><b>Oil seal 35x62x10 mm</b> Shaft seal with dust lip AO</p> <p>ABMS. d 35 x D 62 x W 10 mm</p> <p>NBR -40 ° to 100 ° C</p>

	<p>for sealing rotating shafts and axles sealed in a radial direction for both right and left rotation</p> <p>German standard DIN 3760 International Standard ISO 6194</p>
<p>New</p> 	<p><b>Oil Seal 40x52x7 mm</b> Shaft seal with dust lip AO</p> <p>ABMS. d 40 x D 52 x W 7</p> <p>NBR -40 ° to 100 ° C for sealing rotating shafts and axles sealed in a radial direction for both right and left rotation</p> <p>German standard DIN 3760 International Standard ISO 6194</p>