



Solenoid Valve, (namur standart)



Product code : T-NM 52 W 1S ,1/4"-5/2

Brand : TORK

Solenoid Valve, (namur standart)

TORK, 1/4" - 5/2 with single coil, spring return

Namur solenoid valve T-NM 52W 1S Serie ,is used double acting pneumatic rotary actuator.

application ,is used double acting pneumatic rotary actuator

coil voltage 230/220 V AC,110V,24V,12V AC, 24V,12V DC

prection class IP 65 , T-SB2 Serie ,standard

on request Exproof atex T-ExSB2 Serie , E Ex md II T4

size-way	order type	features	pressure	temperature
G (BSP)		single coil	bar	C degree
1/4" - 5/2	T-NM52W1S	namur standard	2.....10 bar	-10.....80



solenoid valve, (namur type)



Product code : T-NM 32 W 1S ,1/4-3/2 tek bobinli

solenoid valve, (namur type)

TORK,	1/4" - 3/2 single coil, spring return
Namur solenoid valve	T-NM 32W 1S Serie ,is used single acting pneumatic rotary actuator.
application	,is used single acting pneumatic rotary actuator
coil voltage	230/220 V AC,110V,24V,12V AC, 24V,12V DC
prection class	IP 65 , T-SB2 Serie ,standard
on request	Exproof atex T-ExSB2 Serie , E Ex md II T4

size-way	order type	features	pressure	temperature
G (BSP)		single coil	bar	C degree
1/4" - 3/2	T-NM32W1S	namur standard	2.....10 bar	-10.....80



Solenoid Valve, (Explosion- proof) Namur



Product code : T-Ex.NM 52 W 1S ,1/4"-5/2

Brand : TORK

Solenoid Valve, (Explosion- proof) Namur

TORK, 1/4"-5/2,single coil, spring return

Namur solenoid valve T-ExNM 52W 1S Serie ,is used double acting pneumatic rotary actuator.

application ,is used double acting pneumatic rotary actuator

coil voltage 230/220 V AC,110V,24V,12V AC, 24V,12V DC

prection class Exproof atex T-ExSB2 Serie , E Ex md II T4

size-way	order type	features	pressure	temperature
G (BSP)		single coil	bar	C degree
1/4" - 5/2	T-ExNM52W1S	namur standard	2.....10 bar	-10.....80

coils



Product code : T-SB20,.....T-SB25

coils

TORK,

for 5/2 and 3/2 way solenoid valves

Type: T-SB20 6VA 5W

VOLTAGE: 50-60Hz.

T-SB 20

220V AC

T-SB 21

110 V AC

T-SB 22

24V AC

T-SB 23

12V AV

T-SB 24

24V DC

T-SB 25

12 V DC

cupper wire

H class 180 C degree

prection class

IP 65 with plug DIN 40050

plug

DIN43650 PG9