

	Weight g/m ²	Tear strenght		AirPermeability Δp 200 Pa l/dm ² min	Temperature resistance
		Lenght	Across		
PES 350	350	100	80	350	140
PES 400	400	100	80	270	140
PES 400A	400	100	80	260	140
PES450	450	100	80	245	140
PES 500	500	100	80	220	140
PES 500A	500	100	80	220	140
PES 550	550	100	80	180	140
PES 51/01	10	120	120	100	140
MICRO					
PP 400	400	45	48	250	100
PP 550	550	45	48	160	100
DT 500	500	46	45	200	135
DT 550	550	46	45	160	135
DT 500A	500	46	45	200	135
NO 400	400	32	30	225	210
NO 500	500	32	30	190	210
NO 550	550	32	30	160	210
CO 30	245	60	54	460	120
CO 20	250	60	54	460	120
CO 40	315	90	75	75	120
PP 38/19	305	240	240	165	100

EL

News

Електролюкс
Electrolux
Macedonia
Palenzo

PES 38/19	305	240	240	165	135
PES 400	400	230	185	88	135
DT 40/19	300	160	140	54	135
FRS 400	400	46	45	290	135
FRS 500	500	46	45	210	135
ADDITIONAL TREATMENT				FORM	
K2 smoothed				filter bags on drawing or sample	
SC hydrophobic					
SG oleophobic					
TE teflonized					
O1 with microporous membrane					
A antistatic effect					