

## Videojet 6210

## Thermal Transfer Overprinter

# Consistent, High Resolution Variable Images At An Affordable Price

- Consistent, high quality print
- Real-time variable data
- Long production runs
- Simple to operate
- Low cost of ownership

The Videojet 6210 offers a proven and cost-effective solution for users ready to migrate to a digital solution from a non-digital solution such as hot stamp or roller coders.

The Videojet 6210 delivers 300 dpi images on a wide variety of flexible packaging materials. This efficient printer is well-suited for applications in snack food, bakery, confectionery, frozen and refrigerated foods, bagged fresh vegetables and dried fruits markets.

The internal clock function in the Videojet 6210 provides on-line printing of variable and real-time data such as best by date, time, batch and lot codes, shift code and production line ID.

The Videojet 6210 features a proven, clutchless ribbon drive that is highly reliable. Ribbon tension is consistently maintained, virtually eliminating ribbon-related downtime. A 600 meter ribbon length capacity requires less frequent ribbon changes than hot stamp or other competitive TTO equipment.


The intuitive, graphical user interface incorporate easy to learn, icon-based controls and a WYSIWYG image display to reduce set up errors. Two to three keystrokes, and you're ready to print!

The Videojet 6210 is designed to operate efficiently. The bi-directional ribbon drive allows unused ribbon to be recaptured after each print, providing more prints per roll and a low cost of ownership.





## **Dimensions**



## Videojet TotalSource® Service

The **Total**Source program is the finest and most complete technical support system in the business. These services include everything from expert applications assistance, operator training and a full spectrum of maintenance services. The **Total**Source program ensures total customer satisfaction. **Support when you need it** 

© 2007 Videojet Technologies Inc. – All rights reserved. Videojet Technologies Inc.'s policy is one of continued product improvement. We reserve the right to alter design and/or specifications without notice. Videojet and Total/Source are registered trademarks of Videojet Technologies Inc. Windows is a registered trademark of Microsoft Corporation. TrueType is a registered trademark of Apple Computer. Inc.





VIDEOJET,

## **Specifications**

#### **Printhead**

• 32 mm, 300 dpi (12 dots / mm)

#### Print Area

• 32 mm x 30 mm (1.3" x 1.2")

#### **Printing Modes**

Continuous & Intermittent modes in the same machine

#### **Print Speed**

- Intermittent: 50 mm/sec. to 200 mm/sec. (2.0"/sec to 7.9"/sec)
- Continuous: 40 mm/sec. to 500 mm/sec. (1.6"/sec to 19.7"/sec)

#### **Operator Interface**

- 5.7" Color QVGA CSTN (240 x 320 pixels) LCD and touch screen
- WYSIWYG print preview
- · On-board diagnostics
- 3 levels of password protection
- Multiple language support

#### **Ribbon Drive**

- · Solid-state, clutchless bi-directional ribbon drive, including
  - Ribbon break detection
  - · End of reel detection
  - Ribbon consumption indication
  - Ribbon Save mode: Interleave (50% saving of ribbon)

#### **Printing Capabilities**

- Full downloadable font support using Windows® TrueType® fonts
- · Fixed and variable text and numeric data
- User entered text and numeric data (including Chinese)
- Flexible date / time formats (based on internal real time clock)
- Auto best before date calculations
- · Flexible Shift code formats

#### Ribbon Length

• 600 meters (656 yds.) available in variety of grades and colors

## Ribbon Widths

• 22 mm and 33 mm (0.9" and 1.3")

## **Image Design Management**

- Created using CLARiSOFT for VJ6210
- Stored locally in printer's internal memory (128MB capacity)
- Loaded via USB memory stick or RS232

## **Remote Coder Configuration Software**

• Clarity Configuration Manager (included)

## **External Communications**

• USB memory stick, RS232 (binary communications only)

#### **External Inputs**

- Print Go
- Inhibit Print
- Quadrature encoder (single phase not supported)

## **External Outputs**

- Fault
- Warning
- Busy
- Printing

## Air Supply

• 4-6 Bar, locally regulated

## **Power Supply**

• 90-240 VAC 50/60Hz

### **Operating Temperature**

• 5°- 40° C (41°-104°F)



800-843-3610 • www.videojet.com • info@videojet.com

Videojet Technologies Inc. • 1500 Mittel Boulevard Wood Dale IL • 60191-1073 • USA

Phone: 630-860-7300 • Fax: 630-616-3623