

Industrial Heated Walkway Mats

Product Specifications

Surface

Thickness.....1/2"
 Chevron Height.....1/8"
 Grommet Size (Inner Diameter)3/8"
 Material..... Reinforced natural rubber

Heating Element

Voltage..... 120Vac or 240Vac
 Power Density..... 38 - 40 Watts/SF

In-line Safety Device/Power Cord

Service voltage 120Vac or 240Vac
 Circuit breaker rating..... 15A
 GFCI trip level 6mA
 Cold lead length..... 6 ft
 Cord gauge 14/3 SJTW



Model	Size	Volt	Watts	Amps	Weight	MSRP
HTM24-5	24" x 5'	120	320	2.7	21 lbs.	\$328.13
HTM24-5B	24" x 5'	240	320	1.3	21 lbs.	\$337.50
HTM24-10	24" x 10'	120	615	5.1	41 lbs.	\$656.25
HTM24-10B	24" x 10'	240	615	2.6	41 lbs.	\$675.00
HTM24-15	24" x 15'	120	970	8.1	61 lbs.	\$984.38
HTM24-15B	24" x 15'	240	970	4.0	61 lbs.	\$1,012.50
HTM24-20	24" x 20'	120	1,300	10.8	81 lbs.	\$1,312.50
HTM24-20B	24" x 20'	240	1,300	5.4	81 lbs.	\$1,350.00
HTM36-5	36" x 5'	120	457	3.8	33 lbs.	\$492.19
HTM36-5B	36" x 5'	240	457	1.9	33 lbs.	\$506.25
HTM36-10	36" x 10'	120	964	8.0	66 lbs.	\$984.38
HTM36-10B	36" x 10'	240	964	4.0	66 lbs.	\$1,012.50
HTM36-15	36" x 15'	240	1,471	6.1	99 lbs.	\$1,518.75
HTM36-20	36" x 20'	240	1,978	8.2	132 lbs.	\$2,025.00
HTM48-6	48" x 6'	120	735	6.1	60 lbs.	\$850.00
HTM48-6B	48" x 6'	240	735	3.1	60 lbs.	\$875.00

