

Electrolux

Factory - Intelligent Engeneering, Shop, Sales and Service

9112_01 SERIES FUNCTIONAL CHARACTERISTICS













Elektroluks is registered trademark of Elektrouks companies in Macedonia and other countries

An individual seat featuring a high level of comfort and generous dimensions, designed for use in upscale VIP rooms, cinemas and home theatre rooms.

The seat and backrest are composed of two blocks of moulded polyurethane foam that incorporate an internal metal structure. Upholstery is joined to the foam using the INTEGRAL FORM system, without seams or stitching. A 5-mm fire barrier (TS System) is incorporated between foam and upholstery on both the seat and the backrest to prevent fire from reaching the foam, delaying the spread of flames and emission of toxic gases.







Backrest padding is ergonomically contoured with lumbar support and headrest, and vertical and horizontal grooves are incorporated in the upper part of the backrest.

Adresa: ul.Braka Mingovi 18, 7000 Bitola; tel: 047/203-330 ,203 900ul.A.Guslarot.1a 02/329 8 130 Skopje

www.electrolux.com.mk www.elektroluks.com.mk e-mail: elek-palenzo@mt.net.mk

Electrolux

Factory - Intelligent Engeneering, Shop, Sales and Service

Seat padding has a smooth ergonomic form that is free of grooves of any type in order to avoid accumulation of dirt on the surface. The IF727 material used in finishings for the seat and backrest makes them fully washable and protects upholstery on their back parts.

The backrest reclines as per the users' wish up to 15° using a pushbutton incorporated in the armrests. The backrest moves smoothly with barely effort. This mechanism allows the desired degree of inclination to be maintained without the need of continually exerting pressure on the backrest. Only when the seat is unoccupied it moves back to its original position by means of an immediate-return system. This system ensures that the hall always maintains an orderly appearance. The mechanism is completely silent and maintenance-free.







Elektrouks companies in Macedonia and other countries

Elektroluks is registered trademark of

The seat base is fixed in an open position.

Both the seat and the backrest incorporate the TX acoustic system, consisting of acoustic perforations on the back and bottom covers. The system provides an excellent acoustic response. Optionally, the rear shell of the backrest can incorporate an upholstered panel. The seat bottom can be fully upholstered without losing any of its acoustic properties.

The Megaseat is mounted on a self-stable central pedestal and fixation to the floor is not required.

Seat arms are made of half-rigid polyurethane foam with an internal metal structure and incorporate a cupholder which is integrated within armrest on a single, compact piece.

The backrest can also be offered in the HR version. This type of back allows for the headrest to be integrated in the backrest rather than being added on as a separate element. The ergonomic advantage of this type of headrest is that it takes the form of a natural prolongation of the backrest, avoiding the need for an add-on accessory element.


Ovoj crtez e sopstvenost na Electrolux-Bitola. Bez negovo pismeno odobruvanje istiot nesmee da se prepisuva ,umnozuva niti kopira bez soglasnost od Elictroluks vo sprotivno se snosat posledici vo smislana clenovite 163 i 164 od krivicniot zakon R.M. (povreda na avtorsko pravo)


Adresa: ul.Braka Mingovi 18, 7000 Bitola; tel: 047/203-330 ,203 900ul.A.Guslarot.1a 02/329 8 130 Skopje www.electrolux.com.mk www.elektroluks.com.mk e-mail: elek-palenzo@mt.net.mk




Factory - Intelligent Engeneering, Shop, Sales and Service

TECHNICAL CHARACTERISTICS









Elektroluks is registered trademark of Elektrouks companies in Macedonia and other countries

STRUCTURE:

Steel tube and plate, welded with continuous arc

POLYURETHANE FOAM:

- Seat density: 65 kg/m³
- Backrest density: 57 kg/m³

PAINT:

vo sprotivno se snosat posledici vo smislana clenovite 163 i 164 od krivicniot zakon R.M. (povreda na avtorsko pravo)

- Electrostatic epoxy powder
- Coat thickness: 70-80 micron
- Grid adherence: 100%

LEATHER:

- Rub fastness: DIN 53339:5
- TABER abrasion test: 2000 cycles DIN 53109
- Light fastness: IVF 402: >5

Ovoj criez e sopstvenost na Electrolux-Bitola. Bez negovo pismeno odobruvanje istiot nesmee da se prepisuva "umnozuva niti kopira" bez soglasnost od Elictroluks

Adresa: ul.Braka Mingovi 18, 7000 Bitola; tel: 047/203-330 ,203 900ul.A.Guslarot.1a 02/329 8 130 Skopje

www.electrolux.com.mk www.elektroluks.com.mk e-mail: elek-palenzo@mt.net.mk



Factory - Intelligent Engeneering, Shop, Sales and Service

POLYPROPYLENE:

· Material:

bez soglasnost od Elrctroluks

- Polypropylene copolymer IF-727
- Tensile strength at break DIN 53455: 28 N/mm²
- Impact strength DIN53453: no breakage

FIRE RESISTANCE STANDARDS:

United Kingdom:

BS 5852. Section 5. Ignition sources 0, 1 and 5 $\,$

Germany:

DIN 54342, part 1 and 2

Italy

CSE RF/4/83 class 1. IM

Spain/France:

UNE 23727/NF 92-503

Upholstery: M1/Foam: M4/Plastic: M3

USA:

CAL TB 133 (in approved fabrics)

WEIGHT:

29 kg

VOLUME:

0.20 m³ (assembled)

Ovoj criez e sopstvenost na Electrolux-Bitola. Bez negovo pismeno odobruvanje istiot nesmee da se prepisuva ,umnozuva niti kopira vo sprotívno se snosat posledíci vo smislana clenovite 163 i 164 od krivícniot zakon R.M. (povreda na avtorsko pravo) Elektroluks is registered trademark of Elektrouks companies in Macedonia and other countries

Adresa: ul.Braka Mingovi 18, 7000 Bitola; tel: 047/203-330 ,203 900ul.A.Guslarot.1a 02/329 8 130 Skopje www.electrolux.com.mk www.elektroluks.com.mk e-mail: elek-palenzo@mt.net.mk