

# HDF6015 SERIES

DC FAN

Operating Temp. Range : -20 - +60

Locked Rotor & Polarity Protected

Bearing : Ball Bearing

Housing : Plastic

Fan Blade : Plastic



60 x 60 x 15 mm

Type	Mdel	Rated Voltage VDC	Operate Voltage VDC	Rated Current mA	Rated Input W	Rated Speed rpm	Max Air flow m <sup>3</sup> /min. CFM	Max Static Pressure mmAq inchAq	Noise Level dB(A) / m	Weight gr
Low Speed	* HDF6015L-05LB	5	4.25 - 5.75	175	0.88	2800	0.30 11	1.5 0.06	21	
	* HDF6015L-12LB	12	10.2 - 13.8	75	0.90					
Middle Speed	* HDF6015L-05MB	5	4.25 - 5.75	270	1.35	3350	0.40 14	2.5 0.10	25	42
	* HDF6015L-12MB	12	10.2 - 13.8	110	1.32					
High Speed	* HDF6015L-05HB	5	4.25 - 5.75	360	1.80	4400	0.50 18	4.0 0.16	32	
	* HDF6015L-12HB	12	10.2 - 13.8	135	1.62					

\* Approvals = UL / CUR (UL FOR CANADA) / TUV

