

Item number

Electrolux no.: From 411101 to 411199.

Weight: Varies depending on diameter and size.

Up to 25-pack. Varies with the size of the heater.

Part of

The engine heater is not delivered in the Electrolux WarmUp box. Engine pre-heater is supplied separately because of special adapted solutions for a variety of engines and vehicles.

Installation

Install the heater according to the enclosed installation guide. Install **ONLY** the heater on vehicles listed in the installation guide. Installing Electrolux heaters must only be executed by authorized garages.

Usage

Normal usage - Electrolux engine heaters is dimensioned for "normal usage". Electrolux defines "normal usage" as; 3 connections for 3 hours pr. 24 hour based upon 150 users days a year (5 months a year).

Professional usage - It is necessary to make a yearly function control and if necessary install a new heater to obtain necessary extent of service on emergency vehicles or power supplies where the heater is connected more or less 24/7. This yearly service cost will not be covered by Electrolux AS. Pulse power - Some car parking areas are using interval (pulse) power timers turning the power On and Off several times per hour. Using Electrolux engine heater in suchlike parking facilities will not be considered as "Normal use" and claims will be declined.

Electrolux SafeStart 100-series

Characteristics : Conical head flange Electrolux no: 101-199

This heater can only be installed on cast iron engine blocks.

This heaters flange (B) is shaped as a cup where it is room for the active part (A) of the heating element. The 100-series heater can be suported with more than one conical diameters © 100-series heaters are used for engines with limited open space in the water jacket (**D**). The active heater element (A) has to be surrounded with coolant. Tests made on a medium size vehicle. shows that a 600W 100-serie heater will increase the coolant temperature approx 50°C related to the outdoor temperature when connected in 195 minutes at an outdoor temperature of -17°C or colder. After 195 minutes the system has achieved thermal balance. Longer heating time that 195 minutes at -17_oC or colder is energy dissipation. For that reason we recommend you to use a timer. Please look at the product sheet for Electrolux SmartStart™ or Electrolux

Electrolux AS is conforming to the requirements of both ISO 9001-2008, ISO 14001:2004 and OHSAS 18001:2007. In addition to this, our engine heaters and cables are conforming to the requirements of ISO/ TS 16949:2002.

Technical specifications	
Voltage [V]	230
Power [W]	400-1530
IP rating	IP44
Testing & acceptance	EMKO-TUB(61)NO293/91 EN60335-1,





